

APPENDIX A
2009 Grey Fox Drilling

Hole ID	From (m)	To (m)	Core Width (m)	Zone True Width (m)	Assay grams Au/t	Assay ounce Au/ton
GF09-17						
	56.5	57.5	1.00		2.98	
	57.5	58.5	1.00		0.26	
	58.5	59.5	1.00		0.73	
	59.5	60.5	1.00		0.51	
	60.5	61.5	1.00		1.28	
	61.5	62.5	1.00		5.04	
	62.5	63.5	1.00		26.95	
GF09-17	56.5	63.5	7.00	6.27	5.39	0.16
GF09-18						
GF09-18	75.0	75.6	0.60	0.54	15.57	0.45
	79.4	80.4	1.00		1.37	
	80.4	81.4	1.00		12.00	
	81.4	82.4	1.00		0.62	
GF09-18	79.4	82.4	3.00	2.69	4.66	0.14
GF09-18	86.0	87.0	1.00	0.90	2.81	0.08
GF09-19						
GF09-19	39.0	40.5	1.50	1.19	1.10	0.03
	57.0	58.0	1.00		0.72	
	58.0	59.0	1.00		2.33	
GF09-19	57.0	59.0	2.00	1.58	1.53	0.04
GF09-20						
GF09-20	22.6	24.0	1.40	1.28	1.06	0.03
GF09-20	36.0	37.0	1.00	0.91	8.43	0.25
	39.0	40.0	1.00		2.67	
	40.0	41.0	1.00		0.00	
	41.0	42.0	1.00		3.94	
GF09-20	39.0	42.0	3.00	2.74	2.21	0.06
GF09-20	48.0	49.0	1.00	0.91	277.13	8.08
GF09-20	60.5	62.0	1.50	1.37	1.41	0.04
	66.5	68.0	1.50		1.06	
	68.0	69.5	1.50		0.14	
	69.5	71.0	1.50		29.32	
	71.0	72.5	1.50		0.82	
	72.5	74.0	1.50		1.03	
GF09-20	66.5	74.0	7.50	6.86	6.47	0.19
GF09-21						
	28.5	30.0	1.50		1.41	
	30.0	31.0	1.00		0.03	
	31.0	32.0	1.00		8.78	
	32.0	33.0	1.00		4.30	
GF09-21	28.5	33.0	4.50	4.16	3.38	0.10
	37.5	38.5	1.50		0.73	
	38.5	39.5	1.50		2.11	
	39.5	40.5	1.50		4.03	
	40.5	41.5	1.50		1.61	
GF09-21	37.5	41.5	6.00	5.54	2.12	0.06
	46.0	47.5	1.50		0.94	

	47.5	49.0	1.50		1.10	
	49.0	50.0	1.00		1.41	
	50.0	51.0	1.00		0.96	
	51.0	52.0	1.00		1.51	
	52.0	53.0	1.00		1.58	
GF09-21	46.0	53.0	7.00	6.47	1.22	0.04
	56.0	57.0	1.00		1.30	
	57.0	58.0	1.00		0.00	
	58.0	59.0	1.00		1.03	
	59.0	60.0	1.00		2.19	
GF09-21	56.0	60.0	4.00	3.70	1.13	0.03
GF09-21	74.0	75.0	1.00	0.92	1.03	0.03
GF09-22						
	55.9	56.9	1.00		2.95	
	56.9	57.9	1.00		0.96	
	57.9	58.9	1.00		3.29	
	58.9	59.9	1.00		1.10	
	59.9	60.9	1.00		1.03	
GF09-22	55.9	60.9	5.00	4.83	1.87	0.05
GF09-23						
	41.0	42.0	1.00		5.69	
	42.0	43.0	1.00		7.34	
	43.0	44.0	1.00		10.15	
	44.0	45.0	1.00		14.95	
	45.0	46.0	1.00		28.46	
	46.0	47.0	1.00		7.06	
	47.0	48.0	1.00		3.91	
	48.0	49.0	1.00		1.03	
	49.0	50.0	1.00		0.41	
	50.0	51.0	1.00		1.58	
	51.0	52.0	1.00		5.49	
GF09-23	41.0	52.0	11.00	10.90	7.82	0.23
	61.6	62.6	1.00		6.45	
	62.6	63.6	1.00		5.14	
	63.6	64.6	1.00		14.88	
GF09-23	61.6	64.6	3.00	2.97	8.82	0.26
	66.6	67.6	1.00		4.87	
	67.6	68.6	1.00		4.87	
	68.6	69.1	1.00		18.86	
	69.1	70.1	1.00		1.23	
	70.1	71.0	0.90		4.59	
GF09-23	66.6	71.0	4.90	4.85	6.93	0.20
	93.0	94.0	1.00		2.67	
	94.0	95.0	1.00		4.94	
	95.0	96.0	1.00		4.66	
	96.0	97.0	1.00		6.93	
	97.0	98.0	1.00		4.59	
	98.0	99.0	1.00		2.88	
	99.0	100.0	1.00		0.27	
	100.0	101.0	1.00		1.78	
GF09-23	93.0	101.0	8.00	7.93	3.59	0.10
	108.5	110.0	1.50		1.85	
	110.0	111.6	1.60		2.47	
GF09-23	108.5	111.6	3.10	3.07	2.17	0.06

M GRID NAD 83

Hole ID	T.D.	Northing	Easting	Elevation	Azimuth	Inc. Degrees
GF09-17	131.00	5372912.44	551070.03	291.17	270.00	-58.00
GF09-18	131.00	5372912.57	551082.96	291.46	270.00	-58.00

GF09-19	152.00	5372900.11	551082.48	291.74	270.00	-58.00
GF09-20	131.00	5372887.43	551070.02	292.18	270.00	-58.00
GF09-21	152.00	5372887.39	551082.38	291.89	270.00	-58.00
GF09-22	120.00	5372937.46	551069.65	290.03	270.00	-58.00
GF09-23	162.00	5372900.04	551095.74	291.72	270.00	-58.00

